

BENCHMARK DLT1 TAPE DRIVE

The Benchmark DLT1 tape drive provides the performance of DLT technology at a price that has previously been associated with lower-end DDS drives.



THE POWER OF DLT AT THE PRICE OF DDS

Benchmark Tape Systems now delivers a backup and archive tape subsystem that has enterprise class performance and reliability at a price commonly expected of low-end server products. The Benchmark DLT1 capitalizes on the company's dynamic and highly experienced founding team, plus a technology transfer from Quantum Corporation to deliver this DLT technology to the network server and workstation markets.

Along with leading edge price/performance metrics, Benchmark's DLT1 boasts backward read capability with the popular DLT 4000 format. In addition, virtually all of the popular backup software packages are supported by default because the command set is already established by existing DLT products.

ENTERPRISE RELIABILITY AND PERFORMANCE AT DESKTOP PRICING

Most IT professionals are grappling with the explosive growth of their corporate network data storage requirements with technology that is poorly matched to the job. There is an ever-increasing demand for IT professionals to efficiently manage and procure systems for the enterprise wide network, including workgroups, intranets, and extranets. Benchmark Tape Systems provides a reliable tape solution that safely manages and preserves valuable corporate data. The first of Benchmark's drive family, the DLT1, offers a 40GB native capacity (80GB compressed) and a 3MB/second native transfer rate (6MB/second compressed), providing enterprise reliability and performance at low-end server pricing. The Benchmark DLT1 drive is available as an internally configured unit and as a self-standing enclosed unit.

For those environments that require an automated solution, Benchmark offers the DLT7, a 7-cartridge autoloader. To increase your reliability even more, Benchmark's DLTape™IV media is for use in Benchmark (and all other) DLT drives and libraries.

RELIABILITY AND PERFORMANCE

The reliability of Benchmark's DLT1 is more than designed in; it has already been established by its accomplished lineage. As a natural extension of DLT, the standard of reliability in the industry, we built upon that solid foundation to provide a new benchmark of reliability. The 80GB compressed single cartridge capacity is ideally suited for networked NT servers in small to medium size businesses and individual RISC-based high performance workstations.

Designed with automation in mind, the Benchmark DLT1 drive provides soft unload capability and is perfectly matched with the Benchmark DLT7 autoloader as an ideal automation product. Its backup speed of over 20GB per hour fits within most IT professionals' available backup windows. Add Benchmark DLTape™IV media and you will own a steadfast DLT backup and restore solution — at a DDS price!

SOFTWARE AND PLATFORM CERTIFICATION

Please check our web site (www.BenchmarkTape.com) for the latest Benchmark Tape Systems Compatibility Guide for a complete list of application software packages and hardware platforms compatible with the Benchmark DLT1 and Benchmark DLT7.

We welcome you to visit the site regularly for the latest information on all Benchmark Tape Systems products.

BENCHMARK
TAPE SYSTEMS



Unylogix Technologies Inc.

Tel: (514) 253-5200

Email: info@unylogix.com

web site: www.unylogix.com

BENCHMARK DLT1 TAPE DRIVE

FUNCTIONAL / TECHNICAL SPECIFICATIONS

Performance Specifications

Sustained Transfer Rate	
Native	3.0 MB/sec
Compressed	6.0 MB/sec ¹
Burst Transfer Rate	
Synchronous	20 MB/sec
Capacity	
Native	40 GB
Compressed	80 GB ¹
Average File Access	68 seconds
Interface	
	Wide Ultra SCSI
	Low Voltage Differential (LVD)

Benchmark DLT1 Format Specifications

Recording Format	168 tracks (84 logical track pairs)
Recording Density	123Kbpi
Track Density	336 tpi
Encoding Method	RLL 1,7
Data Compression	DLZ

Reliability Specifications

MTBF	>200,000 hours
Head Life	>30,000 hours
Uncorrected Error Rate	1 x 10 ¹⁷ bits read
Undetected Error Rate	1 x 10 ²⁷ bits read

Physical Specifications

Internal Dimensions – inches (mm)	
Height	3.40 (86.36)
Width	5.75 (144.8)
Length	7.99 (202.95)
Weight – pounds (kg)	2.9 (1.32)

Enclosure Dimensions – inches (mm)	
Height	3.94 (100.08)
Width	8.38 (212.85)
Length	10.44 (277.88)
Weight – pounds (kg)	8.7 (3.94)

Environmental Limits

Operating Temperature F (C)	50 to 104 (10 to 40)
Non-condensing Humidity	20% to 80%
Altitude (maximum)	30,000

Non-Operating	
Temperature F (C)	-40 to 151 (-40 to 66)
Non-condensing Humidity	10% to 95%
Altitude (maximum)	30,000

Power Specifications	
Voltage (DC)	+5v, +12v
Power Consumption (typical)	15 watts

Media/ Format Compatibility

Benchmark DLTtape IV	40 GB native capacity
Benchmark DLT Cleaning Tape	20 uses
Read Compatible with the DLT 4000 format	

Media Life

Archive Storage	30 years with less than 5% loss in demagnetization (@20 ^o C and 40% non-condensing humidity)
Durability	1,000,000 head passes

¹ – Actual capacity & transfer rate is highly dependent on data type



BENCHMARK
TAPE SYSTEMS



Unylogix Technologies Inc.
Tel: (514) 253-5200
Email: info@unylogix.com
web site: www.unylogix.com

Document #000535-01
DLTape is a trademark of Quantum Corporation.